

Description

Sabaclean products are universal cleaning agents and can be used in combination with specific SABA adhesives. See the product sheet for the adhesive in question.

Areas of application

- cleaning of the materials to be bonded
- cleaning/flushing of equipment
- removal of adhesive residues

Technical details*

Base	organic flammable solvent
Viscosity (EN 12092)	approx. 10 mPa.s
Density (EN ISO 2811-2)	approx. 0.80 g/ml
Flash point	below 0 °C
Application temperature of adhesive	minimum approx. +5 °C
Storage and transport temperature	up to approx. +35 °C
Shelf-life	18 months in unopened packaging

* Tested according to SABA Analysis Method unless stated otherwise.

Equipment

In addition to adhesives, SABA also supplies equipment such as glue guns, pressure vessels, pumps, etc. This range of equipment was put together by the SABA Tech Center on the basis of extensive testing and many years of practical experience. The right combination of adhesive and equipment gives you the most efficient application and the highest quality results. For tailored advice please contact our customer service department on telephone number +31 (0) 315 65 89 99 or by email at industry@saba.nl.

Safety recommendations

SABA attaches great value to the safe use and responsible handling of our products. For additional safety information please refer to the relevant SABA safety information sheet.

Important

For an optimal result the surfaces to be bonded should be clean, dry, free of grease, and at application temperature. At a relative air humidity above 70% there is an increased chance of condensation, which can have a detrimental effect upon bonding. When used as a cleaning agent Sabaclean AV can affect varnishes, paints and plastics. Testing beforehand is recommended.

Contact

Our customer service department will be happy to answer all your questions. Please call us on +31 (0) 315 65 89 99 or email us at industry@saba.nl.



SABA Dinxperlo BV

Industriestraat 3 NL7091 DC Dinxperlo PO Box 3 NL7090 AA Dinxperlo T +31(0)315 65 89 99 F +31(0)315 65 32 07 E info@saba.nl www.saba.nl

Our recommendations and operating instructions are based on the current state of the art of knowledge and technology. Buyers and users must assess our products themselves in terms of the desired application and requirements. We are not liable if our products are used without due consideration of our recommendations and/or operating instructions. Furthermore the General Terms & Conditions of SABA Dinxperlo BV apply to our recommendations and operating instructions and the delivery of our products.